

+7 (800) 551-81-13
TECHNOSONUS.RU



ЭЛЕКТРО
АКУСТИКА

 **TECHNO
SONUS**
Audio

КОМПЛЕКТ ВСТРАИВАЕМОЙ АКУСТИКИ

MID/HI

1-10 COX

MID/HI

1-8 COX

MID/HI

2-8

SUB

BASS

Speaker component
Frequency Response, Hz -3dB
Power handling, w(AES)
Horizontal/Vertical Coverage
Sensitivity, db
SPL 1m
Impedance, ohm
Conector

Mid 1-10" 260mm/Hi 1" 44mm
80-18000 Hz
300/45
90/90
97/102
121/118
8/8
2xNeutrik Speakon NL4

Speaker component
Frequency Response, Hz -3dB
Power handling, w(AES)
Horizontal/Vertical Coverage
Sensitivity, db
SPL 1m
Impedance, ohm
Conector

Mid 1-8" 210mm/Hi 1" 25mm
80-18000 Hz
250/30
90/90
97/100
120/115
8/8
2xNeutrik Speakon NL4

Speaker component
Frequency Response, Hz -3dB
Power handling, w(AES)
Horizontal/Vertical Coverage
Sensitivity, db
SPL 1m
Impedance, ohm
Conector

Mid 2-8" 210mm/Hi 1" 34mm
74-18000 Hz
400/60
60/40
96/105
122/122
8/8
2xNeutrik Speakon NL4

Speaker component
Frequency Response, Hz -3dB
Power handling, w(AES)
Sensitivity, db
SPL 1m
Impedance, ohm
Conector

Low 12" 316mm
35-80 Hz
500
91
118
8
2xNeutrik Speakon NL4

SUB BASS



MID/HI 2-8



MID/HI 1-8 COX



MID/HI 1-10 COX



MID/HI HORN 1-10 1-3

Speaker component	Mid 10" 260mm/Hi 3" 75mm
Frequency Response, Hz -3dB	180-18000 Hz
Power handling, w(AES)	400/100
Horizontal/Vertical Coverage	60/40
Sensitivity, db	99/110
SPL 1m	128/132
Impedance, ohm	8/8
Conector	2xNeutrik Speakon NL4

MID BASS 115 FRONT HORN

Speaker component	Low 15" 360mm
Frequency Response, Hz -3dB	68-170 Hz
Power handling, w(AES)	700
Sensitivity, db	103
SPL 1m	132
Impedance, ohm	8
Conector	2xNeutrik Speakon NL4

SUB BASS 118 HYBRID HORN

Speaker component	Low 18" 460mm
Frequency Response, Hz -3dB	35-120 Hz
Power handling, w(AES)	1600
Sensitivity, db	102
SPL 1m	132
Impedance, ohm	8
Conector	2xNeutrik Speakon NL4



